

**Course Name:
Analysis and
Design of
Algorithms**

Topics to be covered

- Divide and Conquer - Merge Sort

Divide and Conquer

- Recursive in structure
 - **Divide** the problem into sub-problems that are similar to the original but smaller in size
 - **Conquer** the sub-problems by solving them **recursively**. If they are small enough, just solve them in a straightforward manner.
 - **Combine** the solutions to create a solution to the original problem

An Example: Merge Sort



Sorting Problem: Sort a sequence of n elements into non-decreasing order.

- ***Divide:*** Divide the n -element sequence to be sorted into two subsequences of $n/2$ elements each
- ***Conquer:*** Sort the two subsequences recursively using merge sort.
- ***Combine:*** Merge the two sorted subsequences to produce the sorted answer.

Original Sequence

Merge Sort – Example

Sorted Sequence



Merge-Sort (A, p, r)

INPUT: a sequence of n numbers stored in array
A

OUTPUT: an ordered sequence of n numbers

```
MergeSort (A, p, r) // sort A[p..r] by divide & conquer
1  if  $p < r$ 
2    then  $q \leftarrow \lfloor (p+r)/2 \rfloor$ 
3      MergeSort (A, p, q)
4      MergeSort (A, q+1, r)
5      Merge (A, p, q, r) // merges A[p..q] with A[q+1..r]
```

Initial Call: MergeSort(A, 1, n)

Procedure Merge

Merge(A, p, q, r)






```
1  $n_1 \leftarrow q - p + 1$ 
2  $n_2 \leftarrow r - q$ 
3   for  $i \leftarrow 1$  to  $n_1$ 
4     do  $L[i] \leftarrow A[p + i - 1]$ 
5   for  $j \leftarrow 1$  to  $n_2$ 
6     do  $R[j] \leftarrow A[q + j]$ 
7    $L[n_1 + 1] \leftarrow \infty$ 
8    $R[n_2 + 1] \leftarrow \infty$ 
9    $i \leftarrow 1$ 
10   $j \leftarrow 1$ 
11  for  $k \leftarrow p$  to  $r$ 
12    do if  $L[i] \leq R[j]$ 
13      then  $A[k] \leftarrow L[i]$ 
14            $i \leftarrow i + 1$ 
15      else  $A[k] \leftarrow R[j]$ 
16            $j \leftarrow j + 1$ 
```

Input: Array containing sorted subarrays $A[p..q]$ and $A[q+1..r]$.

Output: Merged sorted subarray in $A[p..r]$.

Sentinels, to avoid having to check if either subarray is fully copied at **each step**.

Merge – Example



Correctness of Merge

Merge(A, p, q, r)

```
1  $n_1 \leftarrow q - p + 1$ 
2  $n_2 \leftarrow r - q$ 
3   for  $i \leftarrow 1$  to  $n_1$ 
4     do  $L[i] \leftarrow A[p + i - 1]$ 
5   for  $j \leftarrow 1$  to  $n_2$ 
6     do  $R[j] \leftarrow A[q + j]$ 
7    $L[n_1 + 1] \leftarrow \infty$ 
8    $R[n_2 + 1] \leftarrow \infty$ 
9    $i \leftarrow 1$ 
10   $j \leftarrow 1$ 
11  for  $k \leftarrow p$  to  $r$ 
12    do if  $L[i] \leq R[j]$ 
13      then  $A[k] \leftarrow L[i]$ 
14            $i \leftarrow i + 1$ 
15      else  $A[k] \leftarrow R[j]$ 
16            $j \leftarrow j + 1$ 
```

Loop Invariant for the *for* loop

At the start of each iteration of the *for* loop:

Subarray $A[p..k - 1]$ contains the $k - p$ smallest elements of L and R in sorted order. $L[i]$ and $R[j]$ are the smallest elements of L and R that have not been copied back into A .

Initialization:

Before the first iteration:

- $A[p..k - 1]$ is empty.
- $i = j = 1$.
- $L[1]$ and $R[1]$ are the smallest elements of L and R not copied to A .

Correctness of Merge

Merge(A, p, q, r)

```
1  $n_1 \leftarrow q - p + 1$ 
2  $n_2 \leftarrow r - q$ 
3   for  $i \leftarrow 1$  to  $n_1$ 
4     do  $L[i] \leftarrow A[p + i - 1]$ 
5   for  $j \leftarrow 1$  to  $n_2$ 
6     do  $R[j] \leftarrow A[q + j]$ 
7    $L[n_1 + 1] \leftarrow \infty$ 
8    $R[n_2 + 1] \leftarrow \infty$ 
9    $i \leftarrow 1$ 
10   $j \leftarrow 1$ 
11  for  $k \leftarrow p$  to  $r$ 
12    do if  $L[i] \leq R[j]$ 
13      then  $A[k] \leftarrow L[i]$ 
14            $i \leftarrow i + 1$ 
15      else  $A[k] \leftarrow R[j]$ 
16            $j \leftarrow j + 1$ 
```

Maintenance:

Case 1: $L[i] \leq R[j]$

- By LI, A contains $p - k$ smallest elements of L and R in sorted order.
- By LI, $L[i]$ and $R[j]$ are the smallest elements of L and R not yet copied into A .
- Line 13 results in A containing $p - k + 1$ smallest elements (again in sorted order). Incrementing i and k reestablishes the LI for the next iteration.

Similarly for $L[i] > R[j]$.

Termination:

- On termination, $k = r + 1$.
- By LI, A contains $r - p + 1$ smallest elements of L and R in sorted order.
- L and R together contain $r - p + 3$ elements. All but the two sentinels have been copied back into A .

Analysis of Merge Sort

- Running time $T(n)$ of Merge Sort:
- Divide: computing the middle takes $\Theta(1)$
- Conquer: solving 2 subproblems takes $2T(n/2)$
- Combine: merging n elements takes $\Theta(n)$
- Total:

$$T(n) = \Theta(1) \quad \text{if } n = 1$$

$$T(n) = 2T(n/2) + \Theta(n) \quad \text{if } n > 1$$

$$\Rightarrow T(n) = \Theta(n \lg n)$$